

STANLEY®



CR27 CIRCLE POLE SAW

The CR27 circular saw is perfect for right-of-way crews, utilities, parks departments, and groundskeepers. Its Blade Brake feature reduces blade coast time to 2.5-5.0 seconds, which is much faster than the 15 seconds or more required by tools without blade brakes. This lightweight saw has a fiberglass pole for easy handling in tight spaces and an integral motor that ensures long-lasting, dependable service. The angled head, created by the integral motor and motor yoke, provides better visibility while cutting and allows for a more natural working posture, reducing fatigue. The motor's new position in relation to the handle also creates a blade forward position that minimizes torque reaction to the operator. Additionally, the blade is secured with a unique double cone-lock nut for added safety.

CR27 CIRCLE POLE SAW

FEATURES

- If the trigger guard is removed the saw is deactivated
- A “Dual Spool” feature permits the user to operate the saw from either open or closed center circuits
- All saws are individually dielectric tested before leaving the factory
- Ideal for use by right-of-way crews, arborists, utilities, parks departments, grounds keepers, and forest trail maintenance crews

SPECIFICATIONS

CAPACITY	9 IN. BLADE, EPOXY HANDLE / 23 CM BLADE, EPOXY HANDLE
WEIGHT (WITH BLADE)	9.76 LBS / 4.4 KG
LENGTH (WITH BLADE)	79 IN. / 200.7 CM
HYDRAULIC PRESSURE	1000 - 2000 PSI. / 70 - 140 BAR
FLOW RANGE	5 - 7 GPM / 19 - 26 LPM
OPTIMUM FLOW	7 GPM / 26 LPM
PORTING	-8 SAE O-RING
CONNECTOR SIZE AND TYPE	3/8 IN. MALE PIPE ADAPTER
MOTOR	INTEGRAL

ORDER INFORMATION

PART NO.	DESCRIPTION
CR27891	O.C./C.C. DUAL SPOOL, 5 FT/152 CM EPOXY HANDLE AND BLADE BRAKE

ACCESSORIES

PART NO.	DESCRIPTION
34356	9 IN./22.9 CM CIRCLE SAW BLADE - 24 TOOTH
34653	TOOTH SETTING TOOL FOR 34356 BLADE
11299	FILE GUIDE WITH 7/32 IN. ROUND FILE
05005	CERTIFIED NON-CONDUCTIVE DUAL OIL RESISTANT PIGTAILS, 3/8 IN. X 10 FT. LESS COUPLERS (3 LB. 8 OZ.)
03971	3/8 HTMAFLAT FACE COUPLING SET, 3/8 NPTPORT (11 OZ.)