

# STANLEY®



## HP8 POWER UNIT

The HP8 hydraulic power unit is engineered for continuous professional use and is optimized to deliver ideal flows and pressures to both Type 1 and Type 2 hydraulic tools. Its powerful 18 HP Briggs & Stratton engine and best-in-class cooling system deliver the power and heat rejection pros need to keep tools working uninterrupted all day in all types of conditions. The HP8 features an intuitive throttle selector which makes changing flow rates very easy. Its feature-rich, dependable operation make the HP8 the workhorse of the industry.

# HP8 POWER UNIT

## FEATURES

- Type II or Type III hydraulic circuit with superior cooling
- Tool circuit lockout during startup - safety feature
- Lift & Latch handle with fold-up side handles
- Quartz hour meter on control panel records engine run time
- 35-AH sealed, non-spillable, no maintenance battery located in covered compartment
- In tank hydraulic filter with dipstick and easy access filter replacement

## SPECIFICATIONS

OUTPUT CAPACITY	5 OR 8 GPM / 20 OR 30 LPM
PRESSURE	2000 PSI / 140 BAR
CIRCUIT TYPE	OPEN CENTER
HYDRAULIC RESERVOIR CAPACITY	3 GALLONS / 11.4 LITERS
COUPLERS	HTMA FLUSH FACE
FUEL TANK CAPACITY	5.5 GALLONS / 20.8 LITERS
ENGINE	BRIGGS & STRATTON 18 HP VANGUARD OHV
WEIGHT	330 LBS / 150 KG
LENGTH	35 IN. / 89 CM
WIDTH	21.5 IN. / 54.6 CM
HEIGHT	29 IN. / 74 CM

## ORDER INFORMATION

PART NO.	DESCRIPTION
HP8BA	5 OR 8 GPM BRIGGS & STRATTON 18 HP, CE
HP8BD	5 OR 8 GPM BRIGGS & STRATTON 18 HP

## ACCESSORIES

PART NO.	DESCRIPTION
31848	DUAL HOSE, 50 FT X 1/2 IN. WITH COUPLERS
31972	DUAL HOSE, 25 FT X 1/2 IN. WITH COUPLERS
58633	TWINNED HOSE, 25 FT X 1/2 IN. WITH COUPLERS
58634	TWINNED HOSE, 50 FT X 1/2 IN. WITH COUPLERS
13360	HOSE BASKET KIT
33212	WEATHER COVER

**STANLEY**®

3810 SE Naef Road // Milwaukie, OR 97267 // 833-723-1843 // [www.IndustrialToolsAndAttachments.com](http://www.IndustrialToolsAndAttachments.com)

2025.03.21