

STANLEY®



TJ12 TRACK JACK

The TJ12 is a top-performing track jack with an exceptional power-to-weight ratio, outclassing its competitors. It is designed for durability, with a tool life that is 200% longer than that of leading competitors. The new carry handle improves ergonomics, making it easier to transport from job to job.

TJ12 TRACK JACK

FEATURES AND BENEFITS

- Integrated pump/carry handle increases tool durability and improves ergonomics
- Improved linkage design eliminates potential to bend piston
- Enhanced Disogren O-rings, bushings, and threaded pick-up tube are incorporated to improve the tool's longevity
- Redesigned release knob for quick and easy lowering
- Long-travel pump action means fewer pumps to achieve maximum height
- Internal reservoir bladder allows operation in any position
- 10 tons of lifting force

SPECIFICATIONS

STROKE (TOTAL LIFT)	8.8 IN. / 22.3 CM
AMOUNT OF TRAVEL PER PUMP STROKE	.16 IN. / .4 CM
LIFTING CAPACITY	10 TONS / 9072 KG
WEIGHT	43 LBS / 19.5 KG
OPERATING PRESSURE	7250 PSI / 499 BAR
MAXIMUM HANDLE EFFORT FOR FULL LOADSURE	75 LBS / 334 N
MAXIMUM TOE HEIGHT	1.81 IN. / 4.59 CM
OVERALL COLLAPSED HEIGHT	14.7 IN. / 37.3 CM
BASE WIDTH (STANDARD VERSION)	6 IN. / 15.2 CM
BASE WIDTH (NARROW VERSION)	4.5 IN. / 11.4 CM
BASE LENGTH	11 IN. / 27.9 CM

ORDER INFORMATION

PART NO.	DESCRIPTION
TJ12111S	TRACK JACK, INTEGRAL PUMP, HYDRAULIC JACK
TJ12112S	TRACK JACK, INTEGRAL PUMP, NARROW BASE BRIDGE JACK

ACCESSORIES

PART NO.	DESCRIPTION
52813	PUMP HANDLE ASSEMBLY
74864	SERVICE PUMP ASSEMBLY



74864 - Service Pump Assembly

